


brevont

FARO WALL

FAROW.W.35.927



Product Information

Super compact LED luminaire for the enhancement of landscape and architectural details through refined accent lighting effects.

Installation	Wall, floor, ceiling mounting
Size / Weight	Ø60 50x66x126 mm / 0.5 Kg
Colour	White RAL9003 / Brass swivel
Body Material	A2 stainless steel with Brass swivel
Screen Material	Tempered glass
Fixing Position	Full orientation capability
Warranty	5 year warranty

Technical Data

Light Source	LED
CCT (K) / CRI	2700K / 80 CRI (90 on request)
Luminous Efficacy	97lm/W
Delivered Lumen	1218lm
Beam Angle	35° (wide)
Power Consumption	12.5W
Current	350mA
Ingress Protection	IP67
Impact Resistance	IK08
Driver	Remote (to be ordered separately)
Operating temperature	-30°C to 40°C
Rated life	50,000hrs

Accessories (to be ordered separately)

FAROW.V.B - FARO WALL VISOR BLACK RAL9005
FAROW.V.W - FARO WALL VISOR WHITE RAL9003

FAROW.HL - FARO WALL HONEYCOMB LOUVRE
FAROW.DRIVER.DALI - FARO WALL DRIVER DALI 39W IP20