

ECP60VL 60W

Constant Voltage 24V 60W Non-Dimmable



Product Code ACC.DRV.ECP60VL.24

Models

-24VL

Output Specifications

Output Voltage	124V
Voltage Tolerance	± 5%
Output Current	0-2.5A
Rated Power	60W

Input Specifications

Input Voltage	198-264VAC
Frequency Range	47-63Hz
Inrush Current	<70A
Full Load Efficiency (Typ.)	87%
AC Current (Max.)	0.5A
Power Factor	PF >0.95/230AV (Full Loading)

Protection

Short Circuit	Shut down o/p voltage, re-power onto recover after fault condition is removed
Over Loading	<120%, Shut down o/p voltage, re-power onto recover
Over Temperature	115°C shut down o/p voltage, re-power onto recover
Protection Class	II

Environment

Working Temperature	-20~+45/°C (Refer to derating curve), +80°C (max case temp.)
Working Humidity	0-90% RH

Safety & EMC

Safety Standards	EN613471-1:2015, EN 61347-2-13:2014+A1 EN62493:2015
------------------	---

Safety & EMC

EMS	EN61000-3-2; EN61000-3-3; EN61547
EMF	EN62493-2010
ERP	EN1194-2012

Other Specifications

IP Rating	IP20
Weight	0.2 Kg
Size	170 x 44.5 x 28.2 mm
Packing	255 x 205 x 160 mm (50PCS/CTN)

Mechanical Specifications

