


ALVARO 1 CIRCUIT BLACK TRACK SPOT



Product Code TRK.1C.ALVARO.BLK

Item no.	1007638
Rotating or tilting	Rotary bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling, Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V -50/60Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	160
Level of inrush current	3.5 A
Duration of inrush current	120 µs
Stroboscopic effect (SVM)	0.4
Lumen	740 lm
Colour temperature	2700 Kelvin
Beam angle	32 °
Color	black

The rotating and pivoting ALVARO SPOT shines across the board: quickly and easily mounted on the single-phase high-voltage track system, the new generation impresses with an improved colour reproduction index CRI>90, a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours.

Added to this is the high-quality light that creates a particularly cosy atmosphere in living areas, hotels and restaurants. Ideal for modern lighting concepts, made of high-quality aluminium, quickly installed and available in colour temperatures of 2700K and 3000K

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Length	10.5 cm
Height	10.7 cm
Diameter	5 cm
Net weight	0.24 kg
Gross weight	0.257 kg